



EnviroStraw™
PROVEN REVEGETATION SOLUTIONS



ENVIROSTRAW BFM COMPLETE

A next generation hydromulch that's a hydraulic growth media, bonded fibre matrix and biotic growth amendment all in one - Just add seed and spray.



envirostraw.com.au

ENVIROSTRAW BFM COMPLETE



EnviroStraw™
BFM Complete

A next generation hydromulch that's a hydraulic growth media, bonded fibre matrix and biotic growth amendment all in one – just add the seed and spray.

As global leaders in microbial revegetation, Envirostraw's all-in-one BFM Complete sets another new standard in Australasian hydromulch – for optimal results, simply add seed and spray. Composed of thermally processed natural plant-derived fibre with an included suite of 22 bacteria and fungi (microbes), CRF controlled-release, mineral-based fertiliser, bio-stimulants, probiotics and soil conditioners, BFM Complete meets AS4454-2012 standards for soil conditioners and is enhanced to be native plant-friendly. The unique and world-leading combination of polymers includes naturally derived hydrocolloid bio-friendly polymers and organic water absorbents. BFM Complete forms a bond with the soil surface to create a continuous, porous, absorbent and flexible erosion-resistant mulch matrix that allows for rapid germination and plant growth – providing up to 6 months of outstanding soil surface protection.

↔ Sold in 20 kg bags, with 52 bags packed per standard pallet.



**AUSTRALIAN
MANUFACTURED**



**100%
BIODEGRADABLE**



**MAXIMUM WATER
USE EFFICIENCY**



**AUSTRALIAN
RENEWABLE RESOURCES**

Why you need EnviroStraw BFM Complete

- ✓ Mix up to 50% more mulch fibre per tank
- ✓ Increased coverage area with every tank applied
- ✓ Delivers uniquely reliable and consistent results
- ✓ Significant water saving providing CO2 reductions with water cart movements
- ✓ Provides a long-term and self-sustaining outcome requiring less maintenance
- ✓ Extremely cost competitive, providing improved on-site efficiencies and compliance.



ENVIROSTRAW BFM COMPLETE



APPLICATION GUIDELINES

To ensure proper application rates, measure and clearly mark out the area. For best results, apply BFM Complete in a two-step process from different directions:

- 1. Pass one:** Apply with specified prescriptive agronomic formulations and 50% of the cover crop seed over the measured area, including all native seeds included with BFM Complete.
- 2. Pass two:** Mix the balance of seed and apply BFM Complete, ensuring all shadowing is eliminated and 100% ground cover is achieved.

C-factor: 0.008 for 100% ground cover on a 30 % slope angle 150mm rain event.

Depending upon site conditions, BFM may be applied in a one-step process where all components may be mixed in a single tank load – contact EnviroStraw for further information.

APPLICATION CONSIDERATIONS

SLOPE GRADIENT	APPLICATION RATE IN KGS PER HECTARE
> 4H -1V & < 3H - 1V	3500 kgs
> 3H -1V & < 2H - 1V	4000 kgs
> 2H -1V & < 1H - 1V	5000 kgs
Below ECB or TRM	3500 kgs
As infill for TRM**	4000 kgs

* These application rates are for standard conditions. Designers may wish to increase application rates on rough surfaces or in high rainfall areas.

** Use only approved and tested TRMs





For more information, please contact our sales department.

1300 868 669

sales@envirostraw.com.au

envirostraw.com.au



WARRANTY

EnviroStraw Pty Ltd warrants that its products are free from defects and will perform as stated in this literature. If our product does not meet product specifications, notice of failure must be received within 7 days of failure. EnviroStraw Pty Ltd will not warrant that the product will perform under unlimited circumstances that are caused by soil conditions, installation, and/or weather variables.